

ODP-2-64075-3KF42-MN

Optidrive P2 VFD Datasheet

75 kW, 150 A, 380-480 V, 3PH

**IP20 Variable Frequency Drive with EMC
Filter and TFT Display**



Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	144.1 A
Supply Fuse or MCB (Type B)	200 A

Output Ratings

Motor Output Rating	75 kW (120 HP)
Output Voltage	0 – Supply Voltage
Output Current	150 A

Cable Information

Max Supply Cable Size	150 mm ² (0.23 sq in)
Max Motor Cable Size	150 mm ² (0.23 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard

Dimensions

Size	6B
Height	726 mm (28.58 in)
Width	330 mm (12.99 in)
Depth	320 mm (12.6 in)
Weight	43 kg (94.8 lbs)
Fixings	-

Packaged Dimensions

Height	380 mm (14.96 in)
Width	375 mm (14.76 in)
Depth	785 mm (30.91 in)
Weight	46 kg (101.41 lbs)



Buy this drive or get more information

Find your local sales partner on
invertekdrives.com



How we measure our drives and packaging



Drive Dimensions



Packaging Dimensions



Buy this drive or get more information
Find your local sales partner on
invertekdrives.com

