

ODP-2-44220-3KF4A-MN

Optidrive P2 VFD Datasheet

22 kW, 46 A, 380-480 V, 3PH

IP66 Non Switched Outdoor Variable
Frequency Drive with EMC Filter and TFT
Display



Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	52.4 A
Supply Fuse or MCB (Type B)	63 A

Output Ratings

Motor Output Rating	22 kW (30 HP)
Output Voltage	0 – Supply Voltage
Output Current	46 A

Cable Information

Max Supply Cable Size	16 mm ² (0.02 sq in)
Max Motor Cable Size	16 mm ² (0.02 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Enclosure	IP66 Non Switched Outdoor
Display	TFT Display
PCB Coating	Standard

Dimensions

Size	4
Height	360 mm (14.17 in)
Width	240 mm (9.45 in)
Depth	261 mm (10.28 in)
Weight	9.5 kg (20.94 lbs)
Fixings	4 x M4

Packaged Dimensions

Height	325 mm (12.8 in)
Width	295 mm (11.61 in)
Depth	425 mm (16.73 in)
Weight	11.5 kg (25.35 lbs)



Buy this drive or get more information

Find your local sales partner on
invertekdrives.com

